



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Overhangend rabat"
Wood species	Meranti (<i>Shorea spp.</i>)
Use	Outdoor
Density and thickness	400 kg/m ³ , all 18/12
Variants	According to table 1 footnote g
Dimension Th.xW.	18 mm x 130 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	3

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdv.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Overhangend rabat"
Wood species	Whitewood/Vuren (<i>Picea abies</i>)
Use	Outdoor
Density and thickness	400 kg/m ³ , all 18/12
Variants	According to table 1 footnote g
Dimension Th.xW.	18 mm x 130 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Overhangend rabat"
Wood species	Redwood/Grenen (<i>Pinus sylvestris</i>)
Use	Outdoor
Density and thickness	400 kg/m ³ , all 18/12
Variants	According to table 1 footnote g
Dimension Th.xW.	18 mm x 130 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Halfhoutsrabat"
Wood species	Meranti (<i>Shorea spp.</i>)
Use	Outdoor
Density and thickness	400 kg/m ³ , all 18/8.5
Variants	According to table 1 footnote g
Dimension TxW	18 mm x 127 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	3

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Halfhoutsrabat"
Wood species	Whitewood/Vuren (<i>Picea abies</i>)
Use	Outdoor
Density and thickness	400 kg/m ³ , all 18/8.5
Variants	According to table 1 footnote g
Dimension TxW	18 mm x 127 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Halfhoutsrabat"
Wood species	Redwood/Grenen (<i>Pinus sylvestris</i>)
Use	Outdoor
Density and thickness	400 kg/m ³ , all 18/8.5
Variants	According to table 1 footnote g
Dimension TxW	18 mm x 127 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Schroot"
Wood species	Meranti (<i>Shorea spp.</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 12/8
Variants	According to table 1 footnote g
Dimension Th.xW.	12 mm x 83 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	3

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Schroot"
Wood species	Whitewood/Vuren (<i>Picea abies</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 12/8
Variants	According to table 1 footnote g
Dimension Th.xW.	12 mm x 83 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Schroot"
Wood species	Redwood/Grenen (<i>Pinus sylvestris</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 12/8
Variants	According to table 1 footnote g
Dimension Th.xW.	12 mm x 83 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Schroot"
Wood species	Western Red Cedar (<i>Thuja plicata</i>)
Use	Indoor and outdoor
Density and thickness	350 kg/m ³ , all 12/8
Variants	According to table 1 footnote g
Dimension Th.xW.	12 mm x 83 mm
Fire Class	F
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	2

based on data Houtvademeccum,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Halfhoutsrabat"
Wood species	Western Red Cedar (<i>Thuja plicata</i>)
Use	Indoor and outdoor
Density and thickness	350 kg/m ³ , all 18/8.5
Variants	According to table 1 footnote g
Dimension Th.xW.	18 mm x 127 mm
Fire Class	F
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	2

based on data Houtvademecum,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Boeidelen"
Wood species	Western Red Cedar (<i>Thuja plicata</i>)
Use	Indoor and outdoor
Density and thickness	350 kg/m ³ , all 18-28/18-28
Variants	According to table 1 footnote g
Dimension Th.xW.	18-28 mm x 185-285 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	2

based on data Houtvademeccum,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "V-deel"
Wood species	Meranti (<i>Shorea spp.</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 16/9
Variants	According to table 1 footnote g
Dimension Th.xW.	16-18 mm x 83-108 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	3

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "V-deel"
Wood species	Whitewood/Vuren (<i>Picea abies</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 16/9
Variants	According to table 1 footnote g
Dimension Th.xW.	16-18 mm x 83 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "V-deel"
Wood species	Redwood/Grenen (<i>Pinus sylvestris</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 16/9
Variants	According to table 1 footnote g
Dimension Th.xW.	16-18 mm x 83 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Kraaldeel"
Wood species	Meranti (<i>Shorea spp.</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 12-16/10
Variants	According to table 1 footnote g
Dimension Th.xW.	12-16-18 mm x 83-108 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	3

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdv.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Kraaldeel"
Wood species	Whitewood/Vuren (<i>Picea abies</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 12-16/10
Variants	According to table 1 footnote g
Dimension Th.xW.	12-16-18 mm x 83 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Kraaldeel"
Wood species	Redwood/Grenen (<i>Pinus sylvestris</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 12-16/10
Variants	According to table 1 footnote g
Dimension Th.xW.	12-16-18 mm x 83 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated -“Halfhoutsrabat”
Wood species	Heat-treated “Whitewood/Vuren or Redwood/Grenen”: Lambowood
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , 17/8
Variants	According to table 1 footnote g
Dimension TxW	17 mm x 123 mm
Fire Class	D-s1,d0
Formaldehyde emission	E1
Water vapour permeability	- 65 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	1 - 2

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated -“Channelsiding”
Wood species	Heat-treated “Whitewood/Vuren or Redwood/Grenen”: Lambowood
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , 17/8
Variants	According to table 1 footnote g
Dimension TxW	17 mm x 123 mm
Fire Class	D-s1,d0
Formaldehyde emission	E1
Water vapour permeability	- 65 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	1 - 2

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated -“Overhangend rabat”
Wood species	Heat-treated “Whitewood/Vuren or Redwood/Grenen”: Lambowood
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , 17/8
Variants	According to table 1 footnote g
Dimension TxW	17 mm x 123 mm
Fire Class	D-s1,d0
Formaldehyde emission	E1
Water vapour permeability	- 65 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	1 - 2

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdv.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated -“Bevelsiding”
Wood species	Heat-treated “Whitewood/Vuren or Redwood/Grenen”: Lambowood
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , 17/8
Variants	According to table 1 footnote g
Dimension TxW	17 mm x 123 mm
Fire Class	D-s1,d0
Formaldehyde emission	E1
Water vapour permeability	- 65 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	1 - 2

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Gibodekker"
Wood species	Meranti (<i>Shorea spp.</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 28/20
Variants	According to table 1 footnote g
Dimension Th.xW.	28 mm x 94-120 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	3

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Neuslijst"
Wood species	Meranti (<i>Shorea spp.</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 28/20
Variants	According to table 1 footnote g
Dimension Th.xW.	28 mm x 120-140 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	3

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Neuslijst"
Wood species	Whitewood/vuren (<i>Picea abies</i>)
Use	Indoor and outdoor
Density and thickness	400 kg/m ³ , all 28/20
Variants	According to table 1 footnote g
Dimension Th.xW.	28 mm x 120-140 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	- 60 Wet cup μ -
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based on product tests by Efectis, 2010,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Schroot"
Wood species	MDF (<i>Picea abies/Pinus sylvestris</i>)
Use	Indoor
Density and thickness	600 kg/m ³ , all 9-12/5-9
Variants	According to table 1 footnote g
Dimension Th.xW.	9-12 mm x 86-136 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	n.p.d.
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based data Houtvademeccum and supplier data,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Kraaldeel"
Wood species	MDF (<i>Picea abies/Pinus sylvestris</i>)
Use	Indoor
Density and thickness	600 kg/m ³ , all 9-12/5-9
Variants	According to table 1 footnote g
Dimension Th.xW.	9-12 mm x 86-136 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1
Water vapour permeability	n.p.d.
Thermal conductivity	0.11
Sound absorption	250 to 500 Hz: 0.10/1000 to 2000 Hz: 0.30
Pentachlorophenol release	n.p.d.
Biological durability	4

based data Houtvademeccum and supplier data,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdb.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Schroot"
Wood species	Tricoya (<i>Pinus radiata</i>)
Use	Indoor and outdoor
Density and thickness	700 kg/m ³ , all 12/8
Variants	According to table 1 footnote g
Dimension Th.xW.	12 mm x 83-108 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1, E1, CARB phase 2
Water vapour permeability	n.p.d.
Thermal conductivity	0.11
Sound absorption	n.p.d.
Pentachlorophenol release	n.p.d.
Biological durability	1

based on data Medite,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdv.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Performity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Halfhoutsrabat"
Wood species	Tricoya (<i>Pinus radiata</i>)
Use	Indoor and outdoor
Density and thickness	700 kg/m ³ , all 15/7
Variants	According to table 1 footnote g
Dimension Th.xW.	15 mm x 127 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1, CARB phase 2
Water vapour permeability	n.p.d.
Thermal conductivity	0.11
Sound absorption	n.p.d.
Pentachlorophenol release	n.p.d.
Biological durability	1

based on data Medite,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvd.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Chanel siding"
Wood species	Tricoya (<i>Pinus radiata</i>)
Use	Indoor and outdoor
Density and thickness	700 kg/m ³ , all 15/7
Variants	According to table 1 footnote g
Dimension Th.xW.	15 mm x 130 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1, E1, CARB phase 2
Water vapour permeability	n.p.d.
Thermal conductivity	0.11
Sound absorption	n.p.d.
Pentachlorophenol release	n.p.d.
Biological durability	1

based on data Medite,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.



Lambert van den Bosch

producent en importeur van hout- en mdf producten

Bezoekadres
Rijksweg 39
6718 WK Ede

Telefoon +31 (0)318 51 90 47
E-mail info@lvdv.com
IBAN NL48RABO 0309 3423 76
BIC RABONL2U
BTW NL004827582B01
EORI NL004827582
KVK 30060150

Declaration of Conformity (DoP)



Houthandel Lambert van den Bosch B.V.
Rijksweg 39
6718 WK Ede

Confirms that:

Product description	Un-coated and coated - "Boeidelen"
Wood species	Tricoya (<i>Pinus radiata</i>)
Use	Indoor and outdoor
Density and thickness	700 kg/m ³ , all 15-18/15-18
Variants	According to table 1 footnote g
Dimension Th.xW.	15-18 mm x 195-599 mm
Fire Class	D-s2,d0
Formaldehyde emission	E1, CARB phase 2
Water vapour permeability	n.p.d.
Thermal conductivity	0.11
Sound absorption	n.p.d.
Pentachlorophenol release	n.p.d.
Biological durability	1

based on data Medite,
subject to Factory Production Control,
manufactured according EC Directive 89/106/CEE
(Construction Products Directive),
conform with Harmonized Product Standard:
EN 14915:2006/AC:2007,
when requirements written in Appendix ZA are taken in account.

Ede, 1st June 2021

C.G. van den Bosch
Managing Director – Houthandel Lambert van den Bosch B.V.